



# **THE YELLOW ONE**

**Hi Vis yellow Arc Flash coverall datasheet**

**AHP001-102**

**AHP001-102****ARMOUR**

0161




The following garments comply with the requirements of Directive 89/686/EEC

**PRODUCT DESCRIPTION:  
AHP001-102**

Arc protective and Flame retardant High Visibility Coverall. This conforms to the following standards;

Made from Carrington flameban max 310 fabric Hi Vis yellow  
EN 1149-5:2018(EN 1149-3:2004), EN ISO 20471:2013 + A1:2016 Class 3, EN ISO 11611 Class 1 A1, EN ISO 11612 A1 B1 C1 F1, EN 61482-2 open arc ELIM = 9.4 cal/cm2 and ATPV = 10 cal/cm2EN ISO 11612  
2015

A1,B1,C1,F1

EN ISO 20471  
2013 + A1:2016

Class 3

EN 61482-2  
2020


ELIM = 9.4 cal/cm2

EN ISO 11611  
2015


Class 1, A1

EN 1149-5  
2018Pt.3 :2004  
Charge Decay**Main Fabric:**40% Protex (Modacrylic) / 24% FR Viscose / 20% Polyester / 10% Cotton /  
4% Aramid / 2% Antistatic**CARE INFORMATION**

- Do not bleach, do not boil, do not use soap based products – only detergents.
- Dirty clothing may lead to a reduction in protection
- Company will not accept liability for garments where care labels have been ignored, neglected, defaced or removed.
- Always store in clean dry conditions.
- Do not store in places subject to direct strong sunlight.
- Maximum washes x5

**100%  
INHERENT  
MADE IN UK****CE**  
0161**SIZE CHART**

Garment Sizes	To fit Chest in Inches (A)	To fit Chest in CM (A)	Short leg Body to fit in CM (B)	Regular leg Body to fit in CM (B)	Tall leg Body to fit in CM (B)	Extra Tall leg Body to fit in CM (B)
<b>SMALL</b>	36-38	90-95	162-166	170-174	178-182	185-189
<b>MEDIUM</b>	40-42	100-105	166-170	174-178	184-188	191-195
<b>LARGE</b>	44	110	174-178	178-182	184-188	191-195
<b>X-LARGE</b>	46-48	115-120	174-178	182-186	188-192	195-199
<b>2XL</b>	50-52	125-130	174-178	182-186	188-192	195-199
<b>3XL</b>	54-56	135-140	174-178	186-190	188-192	195-199
<b>4XL</b>	58-60	145-150	174-178	186-190	188-192	195-199
<b>5XL</b>	62-64	155-160	174-178	186-190	188-192	195-199
<b>6XL</b>	66-68	165-170	174-178	186-190	188-192	195-199

**LEG SIZE**

LEG LENGTH	Inside leg in Inches
Short	29
Regular	31
Tall	33
Extra Tall	36

**LIMITATIONS OF USE****Limitations of use:** This garment must always be worn correctly, fully fastened and without defects, to ensure adequate protection. The Garment uses hook and loop fastenings, make sure these are in the closed position and the hook and loop are not exposed during use.**Keep clean:** This garment must be kept clean and it is recommended to make regular comparisons to a new garment.**Disposal:** This garment should be disposed of in a safe and responsible manner.**Storage:** Always store in a clean and dry environment, away from direct sunlight and strong odours.**Aftercare:** Please follow instructions on the care label for washing.**Maximum Wash Cycles:** X5**Repair:** Do not repair. Discard damaged coverall and replace with new.

Please note, the care instructions are not sole factors involved in the longevity and performance of the protective garment. It is the responsibility of the wearer and/or employer to maintain correct usage, storage, care and also carry out, their own risk assessment to ensure this garment meets the level of protection required. The number of cleaning cycles is not the only factor related to the garment. Lifetime will also depend on usage, care, storage, etc.

Discard or clean the garment when dirty, as dirty garments do not offer full protection.

**By Armour Hazard Protection.** Unit 2a,138 Sydenham Road, Birmingham, B11 1DQ Tel: 0121 771 1027

\*Armour Hazard Protection is a registered trademark of Stratford Workwear Limited

**CE type-examination conducted by:**

Altex. Plaza Emilio Sala, 1 ES-03801 Aloy (Alicante). Approved body number 0161

**Module C2 surveillance procedures:**

Altex. Plaza Emilio Sala, 1 ES-03801 Aloy (Alicante). Approved body number 0161

Declaration of Conformity: <https://www.armourhp.com/technical-file-downloads>